

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 March 2005 (31.03.2005)


PCT

(10) International Publication Number
WO 2005/028091 A1

- (51) International Patent Classification⁷: **B01F 3/04**, (74) Agent: BUCHANAN, Elspeth, Victoria; P.L. Berry & Associates, P.O. Box 1250, Christchurch (NZ).
C02F 7/00
- (21) International Application Number: PCT/NZ2004/000218
- (22) International Filing Date: 15 September 2004 (15.09.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 528434 24 September 2003 (24.09.2003) NZ
- (71) Applicant (for all designated States except US): HENLEY INDUSTRIES LIMITED [NZ/NZ]; C/O Tait Ward Adams, 65 Don Street, Invercargill (NZ).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HENLEY, Bruce, Hyndman [NZ/NZ]; 120 Gladstone Terrace, Invercargill (NZ).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: IMPROVED AERATOR AND MIXER



(57) Abstract: A diffuser which includes a cylinder open at one end and closed at the opposite end, the open end of the cylinder being securable to air supply; the wall of the diffuser being formed with a plurality of holes therethrough, each hole having a large diameter on the exterior of the wall of the diffuser than on the interior of the wall of the diffuser; the longitudinal axis of each hole being inclined at an acute angle to both the radius and the longitudinal axis of the diffuser, and the orientation of each hole with respect to the longitudinal axis of the diffuser being such that when the diffuser is rotated about its longitudinal axis in use, the leading edge of each hole is at a higher elevation than the trailing edge of each hole.

WO 2005/028091 A1



— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.